

HI Series Full Colour Indoor Fixed Installation Led Display

Application	Indoor					
Product Model	HI151	HI191	HI261	HI291	HI391	HI481
Pixel Pitch	1.5625mm	1.953mm	2.604mm	2.976mm	3.91mm	4.81mm
Module Size	1000x250mm	1000x250mm	1000x250mm	1000x250mm	1000x250mm	1000x250mm
Module Resolution	160X160	128X128	96X96	84X84	64X64	52X52
Led	SMD1212	SMD1515	SMD2020	SMD2020	SMD2020	SMD2020
Cabinet Size	1000x250mm	1000x250mm	1000x250mm	1000x250mm	1000x250mm	1000x250mm
Cabinet Resolution	640x160	512x128	384x96	336x84	256x64	208x52
Cabinet Weight	6KG	6KG	6KG	6KG	6KG	6KG
Pixel Density	409600pixel/m ²	262144pixel/m ²	147456pixel/m ²	112896pixel/m ²	65536pixel/m ²	43264pixel/m ²
Recommended Viewing Distance	≥1.5m	≥1.9m	≥2.6m	≥2.9m	≥3.9m	≥4.8m
Brightness	600cd/m ²	800cd/m ²	800cd/m ²	800cd/m ²	1000cd/m ²	1000cd/m ²
Max. Viewing Angle	Horizontal 160° Vertical 160°		Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°	Horizontal 140° Vertical 140°
Cabinet Material	Die-casting Aluminum					
Maintenance	Front					
Refresh Rate	≥3840HZ					
Grey Level	14bit					
Input Voltage	220~240VAC					
Max. Power Consumption	≤500W/m ²					
Ave. Power Consumption	≤200W/m ²					
Ingress Protection	IP30					
LED Life Time	≥100,000 hours					
Input	VGA DVI HDMI SDI					

Note: Specifications are subjected to change without notice.

SHENZHEN HONOURLED CO., LTD

Address: Building B1, Zone B, Phase II, Longfa Road Commercial Center, Longyuan Community, Longhua Street, Longhua District, Shenzhen

Tel: +86 198 0657 6268

Email: info@honourled.com