

## **HB Series Full Colour Rental Led Display**

Application	Indoor					Outdoor				
Product Model	HB151	HB191	HB261	HB291	HB391	HB260	HB290	HB390	HB480	
Pixel Pitch	1.5625mm	1.953mm	2.604mm	2.976mm	3.91mm	2.604mm	2.976mm	3.91mm	4.81mm	
Module Size	250X250mm	250X250mm	250X250mm	250X250mm	250X250mm	250X250mm	250X250mm	250X250mm	250X250mm	
Module Resolution	160X160	128X128	96X96	84X84	64X64	96X96	84X84	64X64	52X52	
Led	SMD1212	SMD1515	SMD2020	SMD2020	SMD2020	SMD1415	SMD1415	SMD1921	SMD1921	
Cabinet Size	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	500X500/ 500x1000mm	
Cabinet Resolution	320X320	256X256	192X192	168X168	128X128	192X192	168X168	128X128	104X104	
Cabinet Weight	7KG	7KG	7KG	7KG	7KG	7KG	7KG	7KG	7KG	
Pixel Density	409600pixel/m²	262144pixel/m²	147456pixel/m²	112896pixel/m²	65536pixel/m²	147456pixel/m²	112896pixel/m²	65536pixel/m²	43264pixel/m²	
Recommended Viewing Distance	≥1.5m	≥1.9m	≥2.6m	≥2.9m	≥3.9m	≥2.6m	≥2.9m	≥3.9m	≥4.8m	
Brightness	600cd/m²	800cd/m²	800cd/m²	800cd/m²	1000cd/m²	4000cd/m²	4500cd/m²	5000cd/m²	5000cd/m²	
Max. Viewing Angle					Horizontal 140° Vertical 140°					
Ingress Protection	IP30					IP65/IP54				
Cabinet Material	Die-casting Aluminum									
Maintenance	Front&Rear									
Refresh Rate	≥3840HZ									
Grey Level	14bit									
Input Voltage	220~240VAC									
Max. Power Consumption	≤500W/m²									
Ave. Power Consumption	≤200W/m²									
LED Life Time	≥100,000 hours									
Input		VGA DVI HDMI SDI								

Note: Specifications are subjected to change without notice.

## SHENZHEN HONOURLED CO., LTD

Address: Building B1, Zone B, Phase II, Longfa Road Commercial Center, Longyuan Community, Longhua Street, Longhua District, Shenzhen

Tel: +86 198 0657 6268 Email: info@honourled.com